




ALFRA ROTABEST®-RB35X

35
mm



DRILLING RANGE UP TO Ø 35 MM

RB 35 X

Cutter dimension	Ø 12.0 - 35.0 mm
Cutting depth	50.0 mm
Twist drill	Ø 1.0 - 13.0 mm DIN 1897 short
Counterbore	Ø 10.0 - 40.0 mm
Tapping	-
Arbor	19 mm Weldon shank
Stroke	120 mm
Height adjustment	-
1-speed gearbox On-load speed	450 rpm.
Power consumption	1.100 W
Voltage	230 V 50/60 Hz / 110 V 50/60 Hz
Tool Force (10 mm) / magnetic holding force	2.100 N / 9.000 N
Magnet foot	70 x 185 mm
Weight	10.6 kg

Motor	
Smooth start	✓
Hybrid relays	✓
Slide	
Self-adjusting guides	✓
Operation	
Soft-touch grips	✓
Membrane keyboard	✓
Holder for Allen key	✓
Cord length 5 m	✓
Magnet	
Sensor/LED	✓
Metal rings	✓
Performance and weight optimisation	✓
	✓



Scope of Supply:

- Metal core drilling machine RB 35 x
- Carrying case
- Safety belt
- Coolant equipment
- Operating manual

Prod.-No.

ALFRA Rotabest® RB 35 X	230 Volt	18700
ALFRA Rotabest® RB 35 X	110 Volt	18700.110